19835-217 Winter Jacket

quilted lining - breathable - wind- and waterproof - multi-protective
MASCOT® MULTISAFE

17010

XS	S	M	L	XL	2XL	3XL
4XL						



BREATHABLE WATERPROOF WINDPROOF DIRT RESISTANT ERGONOMIC FIT

- Breathable, wind and waterproof with taped seams.
- Anti-static, acid-resistant and flame-retardant.
- Dirt repellent.
- Form cut sleeves with great freedom of movement.
- Interior zipper at lower back for logo printing / embroidery.
- Extra protection against the cold with an extended back.
- Press studs to attach a hood if required.

Technical info

Two-toned. Fluorescent, with vertical and oblique transverse reflective strips. Dirt resistant. Anti-static, acid-protective and flame retardent. Protects from electric arcs and occasional welding arcs. Breathable, wind and waterproof. Taped seams. Lining of quilt. High collar. Fastening with zip, double storm flap and hidden press studs. Strap for gas alarm. Zipped pocket under storm flap large enough to hold a 9.4-inch tablet. Chest pocket with a zip. Chest pocket with flap and hidden press studs. D-ring. Front pockets with hidden zip. Ergonomically shaped sleeves allow for great freedom of movement. Zip at lower back for logo printing/ embroidery. Extended back. Waist with internal press stud adjustment. Rib (hidden in storm flap) at cuffs. Elastic at cuffs. Supplement the product with a hood, 19144-217 or 19044-217 (see MASCOT® COMPLETE).

User

Main material/upper material

55% modacrylic/39% cotton/5% polyamid/1% carbon fibres
320 g/m²

60 P®

Twill/Ripstop.According to EN ISO 20471, this product is certified to retain its properties with 50 domestic washes.Impregnation is required after each wash to maintain EN 13034 protection.

Industrial care category B3

Certifications

OEKO-TEX STANDARD 100 · EN ISO 11612 · EN ISO 11611 · EN 1149-5 · EN IEC 61482-1-1 · EN 61482-1-2 · EN 13034 · EN343 3 1 X · EN342 3 WP · EN ISO 20471 2 · EN ISO 20471 3 · HIGH-VIS GROUP: A · ProWash®

- OEKO-TEX® STANDARD 100
- EN ISO 11612 (A1, A2, B1, C1, E1, F1)
- EN ISO 11611 - class 1 (A1 + A2)
- EN 1149-5 (tested according to EN 1149-3)
- EN IEC 61482-1-1 (ELIM 16 cal/cm², ATPV 28,2 cal/cm²)
- EN 61482-1-2 APC 2
- EN 13034 (Type 6)
- EN 343 3-1-X
- EN 342 3/WP (2.309 clo)
- EN ISO 20471 - class 2 (XS)
- EN ISO 20471 - class 3
- Hi-Vis Group A
- ProWash®

Logo

Due to the unique properties of the fabric, logo printing is only available through the use of specific transfer types. As this is a safety product, we strongly recommend that MASCOT affix the logo to reduce the risk of errors. Please contact customer service for further information.

The product is certified with a maximum logo area of (S-4XL) 0,0200 m², (XS) 0,3000m². This approved area must not be

exceeded. Logos respectively on the front or back of the product, can only constitute a maximum of 50% of the total approved logo area in order to maintain the EN ISO 20471-certification. Note: The listed area is only a guide to how much space is available for logo placement. In order to maintain the product’s hi-vis class according to EN ISO 20471, the instructions on logo size must be observed.

Logo placement:

- Workwear logo. Special placement. Contact to discuss further