

21090-292 Over Trousers

flame retardant - two-toned - ULTIMATE STRETCH

MASCOT® ACCELERATE MULTISAFE

17010

S	M	L	XL	2XL	3XL	4XL
5XL						

Main material/upper material

36% modacrylic/25% cotton/18% polyamide/9% polyurethane/6% elastolefin/5% aramid/1% carbon fibres

335 g/m²

ULTIMATE STRETCH.Ripstop.Shrinkage max. 3%.According to EN ISO 20471, this product is certified to retain its properties with 25 domestic washes.Impregnation is required after each wash to maintain EN 13034 protection.

Industrial care category B3

- A high level of protection with anti-static, acid protection and flame retardant properties.
- Protects from electric arcs.
- Windproof and waterproof with taped seams.
- Stretch material provides optimal freedom of movement.
- Higher back provides both support and warmth.
- Back support and straps can be removed from the product as needed.
- CORDURA® reinforcements on the front of the leg.

Technical info

Two-toned. Fluorescent with reflective tape. ULTIMATE STRETCH. Anti-static, acid-protective and flame retardent. Protects from electric arcs. Wind and waterproof. Taped seams. Prepared for holster pockets, attachable with the Click Pocket System. Ergonomically formed trouser leg. Belt loops. Fly with zip. Strong, elastic, detachable, adjustable braces. The waistband is higher at the back, to better protect against the cold. Adjustable kneepad pockets with CORDURA fabric. Zip with storm flap on inside of lower legs. The product has a surface treatment that is repellent and resistant to the permeation of sulfuric acid and sodium hydroxide in accordance with EN 13034 Type 6. Co-certified together with kneepad type large in accordance with EN 14404-3.

User

Certifications

- OEKO-TEX® STANDARD 100
- EN 1149-5 (tested according to EN 1149-3)
- EN ISO 11612 (A1, B1, C1, E2, F1)
- EN 13034 (Type 6)
- EN 13034, category K
- EN ISO 24232 4-1-X
- EN 61482-1-2 APC 2
- EN IEC 61482-1-1 (ELIM 30 cal/cm², ATPV 40 cal/cm²)
- EN ISO 20471 - class 2
- Hi-Vis Group Y

Logo

Due to the unique properties of the fabric, logo printing is only available through the use of specific transfer types. As this is a safety product, we strongly recommend that MASCOT affix the logo to reduce the risk of errors. Please contact customer service for further information.

The product is certified with a maximum logo area of 0,2000m². This approved area must not be exceeded. Logos

respectively on the front or back of the product, can only constitute a maximum of 50% of the total approved logo area in order to maintain the EN ISO 20471-certification. Note: The listed area is only a guide to how much space is available for logo placement. In order to maintain the product’s hi-vis class according to EN ISO 20471, the instructions on logo size must be observed.