21410-292 Hood



breathable - wind- and waterproof

MASCOT® COMPLETE

010 17

ONE

Main material/upper material

36% modacrylic/25% cotton/18% polyamide/9% polyurethane/6% elastolefin/5% aramid/1% carbon fibres

335 g/m²



ULTIMATE STRETCH.Ripstop.Shrinkage max. 3%.According to EN ISO 20471, this product is certified to retain its properties with 25 domestic washes.Impregnation is required after each wash to maintain EN 13034 protection.

Industrial care category B3



- A high level of protection with anti-static, acid protection and flame retardant properties.
- Protects from electric arcs.
- These specifications apply when the hood is attached to 21019-292, 21045-292, 21301-292, 21335-292, 21501-292, 21535-292.
- Adjustable elasticated cord at the front, adjustable wire on both sides and regulation at the back.
- Attaches with press studs.

Technical info

Anti-static, acid-protective and flame retardent. Protects from electric arcs and occasional welding arcs. These specifications apply when the hood is attached to 21019-292, 21045-292, 21301-292, 21335-292, 21501-292, 21535-292. Breathable, wind and waterproof. Taped seams. Adjustable elastic drawstring. Attaches with press studs. Adjustable wire on both sides.

User



Certifications

- OEKO-TEX® STANDARD 100

Logo

Due to the unique properties of the fabric, logo printing is only available through the use of specific transfer types. As this is a safety product, we strongly recommend that MASCOT affix the logo to reduce the risk of errors. Please contact customer service for further information.