F0122-771 Safety Shoe

S3S - BOA® Fit System - Dyneema®

MASCOT® FOOTWEAR FLEX



09880

1039	1040	1041	1042	1043	1044	1045
1046	1047	1048				

Main material/upper material

Textile/suede

Size 42: 599 g



E Shock-absorbing | A Antistatic | PS Textile nail protection (Ø=3mm) | WPA Water repellent and breathable | SR Slip resistant | FO Oil and fuel resistant sole | LG Ladder grip

- Water-repellent and extremely durable CORDURA®/Kevlar®/Dyneema® upper.
- Composite toe cap and PU-reinforced scuff cap ensure the necessary protection and make the shoes extra durable.
- A ladder grip beneath the sole ensures optimum grip on the rungs of the ladder and helps prevent slips.
- Very durable, slip-resistant PU outer sole that's heat-resistant up to 140°C.
- Optimum fit thanks to the BOA® Fit System.

Technical info

The front part of the shoe bends flexibly with the foot. Uppers made of durable CORDURA®/Kevlar®/Dyneema®. Opens and fastens with BOA® Fit System, which consists of a rotational dial, lace and guides. Composite toe cap. Toe reinforcement with PU. Nail protection of special textile material. Stabilising multi-functional shank with integrated absorbing cushioning. Shock-absorbing, soft and flexible two-component sole of PU/PU. Non-marking sole – no scuff marks. Suitable for working on the knees. Ladder grip. 5.0mm profile depth. Insole with optimal arch support that can counteract the tendency to flat foot. Shock-absorbing insoles are removable, durable and ergonomic. Textile breathable lining. Sole is oil and petrol resistant. ESD approved to EN IEC 61340-4-3: 2002.

User

♂

Certifications

S3S | SR | FO | LG | ESD | EN ISO 20345

- Safety Class S3S
- Slip resistant (SR)
- Oil and fuel resistant sole (FO)
- Ladder grip (LG)
- Electrostatic discharge (ESD)
- EN ISO 20345: 2022