# F0136-902 Safety Boot

S3S - BOA® Fit System

MASCOT® FOOTWEAR ENERGY

09

| | | | | | | |
|---|---|---|---|---|---|---|
| 0836 | 0837 | 0838 | 1039 | 1040 | 1041 | 1042 |
| 1043 | 1044 | 1045 | 1046 | 1047 | 1048 | |



E Shock-absorbing | A Antistatic | PS Textile nail protection (Ø=3mm) | WPA Water repellent and breathable | SR Slip resistant | FO Oil and fuel resistant sole | SC Scuff cap abrasion

- Durable and water-repellent safety footwear in soft and flexible leather.
- Very durable, slip-resistant  PU outer sole that’s heat-resistant up to 140°C.
- ETPU inserts in the sole effectively absorb shock, protecting your legs and back with every step.
- Composite toe cap and PU-reinforced scuff cap ensure the necessary protection and make the shoes extra durable.
- Optimum fit thanks to the BOA® Fit System.

## Technical info

The front part of the shoe bends flexibly with the foot. Opens and fastens with BOA® Fit System, which consists of a rotational dial, lace and guides. Composite toe cap. Toe reinforcement with PU. MASCOLAYER® textile nail protection. Insert in the midsole of the shock-absorbing lightweight material. Shock-absorbing, soft and flexible two-component sole of PU/PU. Durable non-marking outsole. Upper in breathable high quality full grain leather. Heat resistant sole up to 140°C. Ladder grip. 5.0mm profile depth. Removable insoles with optimal arch support that can counteract flat feet. Sole is oil and petrol resistant. ESD approved to EN IEC 61340-4-3: 2002.

## User

♂ ♀

## Main material/upper material

Full grain leather

Size 42: 676 g



BOA MASCOLAYER®

## Certifications

S3S | SR | FO | SC | ESD | EN ISO 20345

- Safety Class S3S
- Slip resistant (SR)
- Oil and fuel resistant sole (FO)
- Scuff cap abrasion (SC)
- Electrostatic discharge (ESD)
- EN ISO 20345: 2022