# F0661-906 Safety Shoe

S1PS - BOA® Fit System

MASCOT® FOOTWEAR CUSTOMIZED



09

| | | | | | | |
|---|---|---|---|---|---|---|
| 0836 | 0837 | 0838 | 0839 | 1040 | 1041 | 1042 |
| 1043 | 1044 | 1045 | 1046 | 1047 | 1048 | |

## Main material/upper material

Textile

Size 42: 542 g

E Shock-absorbing | A Antistatic | PS Textile nail protection (Ø=3mm) | SR Slip resistant | FO Oil and fuel resistant sole | SC Scuff cap abrasion | HRO Heat-resistant outsole compound

BOA MASCOLAYER®

- Lightweight and flexible shoe with a very durable textile upper.
- Shock-absorbing dual-component PU midsole ensures all-day comfort and stability.
- Slip-resistant rubber outer sole ensures you always have stable footing.
- Optimum fit thanks to the BOA® Fit System.
- Also available in women’s sizes.

## Technical info

The front part of the shoe bends flexibly with the foot. Uppers made of durable fabric. The outer material is breathable and easily leads heat and moisture away from the foot. Opens and fastens with BOA® Fit System, which consists of a rotational dial, lace and guides. Composite toe cap. MASCOLAYER® textile nail protection. Shock-absorbing, soft and flexible insole. Insoles are removable. Midsole made with EVA. Sole made of rubber with extreme slip resistance. Heat resistant sole up to 300°C contact heat. ESD approved to EN IEC 61340-4-3: 2018, EN 61340-5-1: 2016.

## User

♂ ♀

## Certifications

S1PS | SR | FO | SC | HRO | ESD | EN ISO20345

- Safety Class S1PS
- Slip resistant (SR)
- Oil and fuel resistant sole (FO)
- Scuff cap abrasion (SC)
- Heat-resistant outsole compound (HRO)
- Electrostatic discharge (ESD) EN IEC 61340-4-3: 2018, EN 61340-5-1: 2016
- EN ISO 20345:2022 + A1:2024