# F1003-715 Safety Boot



S3S

MASCOT® FOOTWEAR ORIGINALS

5409

| | | | | | | |
|---|---|---|---|---|---|---|
| 1040 | 1041 | 1042 | 1043 | 1044 | 1045 | 1046 |
| 1047 | 1048 | 1049 | 1050 | | | |

## Main material/upper material

Pull-up leather

Size 42: 799 g

E – Shock-absorbing
A – Antistatic
PS – Textile nail protection (Ø–3mm)
WPA – Water repellent and breathable
SR – Slip resistant
FO – Oil and fuel resistant sole

- Classic and timeless rigger boot providing all-round safety and excellent shock-absorption.
- Get a stable grip on all types of surfaces with the boot's slip-safe and self-cleaning outer sole.
- Metal-free with a light composite toe cap and MASCOLAYER® textile midsole.
- Water and dirt repellent upper in oiled leather.
- Comfortable insole provides both support, extra shock-absorption and moisture wicking.

MASCOLAYER®

## Technical info

The front part of the shoe bends flexibly with the foot. Metal free. Composite toe cap. MASCOLAYER® textile nail protection. Stabilising multi-functional shank with integrated absorbing cushioning. Removable insoles with optimal arch support that can counteract flat feet. Textile breathable lining. Insert in the midsole of the shock-absorbing lightweight material. Shock-absorbing, soft and flexible two-component sole of PU/PU. Light, flexible, black PU/PU sole with extreme slip resistance. Non-marking sole – no scuff marks. The sole is oil and petrol resistant. ESD approved to EN IEC 61340-4-3: 2018, EN 61340-5-1: 2016.

## Certifications

S3S SR FO ESD EN ISO20345

- Safety Class S3S
- Slip resistant (SR)
- Oil and fuel resistant sole (FO)
- Electrostatic discharge (ESD) EN IEC 61340-4-3: 2018, EN 61340-5-1: 2016
- EN ISO 20345: 2022

## User

♂