# F1050-902 Safety Shoe

S3S - laces

MASCOT® FOOTWEAR INDUSTRY



09

| | | | | | | |
|---|---|---|---|---|---|---|
| 1039 | 1040 | 1041 | 1042 | 1043 | 1044 | 1045 |
| 1046 | 1047 | 1048 | | | | |

## Main material/upper material

Full grain leather

Size 42: 635 g

**E** Shock-absorbing | **A** Antistatic | **PS** Textile nail protection (Ø=3mm) | **WPA** Water repellent and breathable | **SR** Slip resistant | **SC** Scuff cap abrasion | **FO** Oil and fuel resistant sole

MASCOLAYER®

- Durable and water-repellent safety footwear in soft and flexible leather.
- Very durable, slip-resistant  PU outer sole that’s heat-resistant up to 140°C.
- ETPU inserts in the sole effectively absorb shock, protecting your legs and back with every step.
- Composite toe cap and PU-reinforced scuff cap ensure the necessary protection and make the shoes extra durable.

## Technical info

The front part of the shoe bends flexibly with the foot. Metal free. Lace fastening. Composite toe cap. Toe reinforcement with PU. MASCOLAYER® textile nail protection. Insert in the midsole of the shock-absorbing lightweight material. Shock-absorbing, soft and flexible two-component sole of PU/PU. Durable non-marking outsole. Upper in breathable high quality full grain leather. Heat resistant sole up to 140°C. Ladder grip. Removable insoles with optimal arch support that can counteract flat feet. Sole is oil and petrol resistant. ESD approved.

## Certifications

S3S | SR | SC | FO | ESD | EN ISO 20345

- Safety Class S3S
- Slip resistant (SR)
- Scuff cap abrasion (SC)
- Oil and fuel resistant sole (FO)
- Electrostatic discharge (ESD)
- EN ISO 20345: 2022

## User

♂ ♀