F1102-901 Safety Boot

S3S - BOA® Fit System

MASCOT® FOOTWEAR INDUSTRY

09

1140	1141	1142	1143	1144	1145	1146
1147	1148	1149	1150			



Main material/upper material

Oil Nubuck

Size 42: 766 g

E Shock-absorbing | A Antistatic | PS Textile nail protection (Ø=3mm) | WPA Water repellent and breathable | HRO Heat-resistant outsole compound | SR Slip resistant

SC Scuff cap abrasion | M Metatarsal protection | LG Ladder grip | FO Oil and fuel resistant sole | HI Heat insulation

- Extremely durable safety boot suitable for wearing while welding.
- Metatarsal guards give you extra protection and soften any impact to the foot from dropped or falling objects.
- Rubber outer sole that’s heat-resistant up to 300°C contact heat.
- Reflective features increase your safety during your working day.

Technical info

Opens and fastens with BOA® Fit System, which consists of a rotational dial, lace and guides. Thermal insulating footwear. Metatarsal protection. Protective flap covering BOA® Fit System. Composite toe cap. Nail protection of special textile material. Midsole made with PU. Insoles are removable. Shock absorbing insole. Heel cap. Ladder grip. Sole made of rubber with extreme slip resistance. Sole is oil and petrol resistant. Heat resistant sole up to 300°C contact heat. Reflectors.

User

♂ ♀

Certifications

S3S | HRO | SR | SC | M | LG | FO | HI | ESD | EN ISO20345

- Safety Class S3S
- Heat-resistant outsole compound (HRO)
- Slip resistant (SR)
- Scuff cap abrasion (SC)
- Metatarsal protection (M)
- Ladder grip (LG)
- Oil and fuel resistant sole (FO)
- Heat insulation (HI)
- Electrostatic discharge (ESD)
- EN ISO 20345: 2022