F1111-704 Safety Sandal, electrical protection

SB - BOA® Fit System

MASCOT® FOOTWEAR ELECTROSAFE



09

0836	0837	0838	0839	1040	1041	1042
1043	1044	1045	1046	1047	1048	1049
1050						

Main material/upper material

Polyamide

Size 42: 500 g

E Shock-absorbing | PS Textile nail protection (Ø=3mm) | SR Slip resistant | FO Oil and fuel resistant sole | HRO Heat-resistant outsole compound | EH Electrical hazard protection

- Electrically insulating soles protect you from electrical hazards.
- Shock-absorbing, light and flexible EVA midsoles provide extra comfort all through the working day.
- Rubber outer sole that’s heat-resistant up to 300°C contact heat.
- Composite toe cap and TPU-reinforced scuff cap ensure the necessary protection and make the shoes extra durable.
- BOA® Fit System on the side of the shoe for simple and quick adjustment.

BOA MASCOLAYER®

Technical info

Developed with the electric vehicle and energy industry in mind with special electrically insulated soles. Dissipative of electrical hazards. Lightweight. Breathable. Opens and fastens with BOA® Fit System, which consists of a rotational dial, lace and guides. Composite toe cap. TPU toe reinforcement. MASCOLAYER® textile nail protection. Shock-absorbing, light and flexible insole. Insoles are removable. Shock-absorbing EVA midsole. Slip resistant rubber outsole. The sole is oil and petrol resistant. Heat resistant sole up to 300°C contact heat.

Certifications

SB | PS | SR | FO | HRO | EH — EN ISO 20345

- Safety Class SB
- Textile nail protection (Ø=3mm) (PS)
- Slip resistant (SR)
- Oil and fuel resistant sole (FO)
- Heat-resistant outsole compound (HRO)
- Electrical insulation, ASTM F2413-24 (EH)
- EN ISO 20345: 2022

User

♂ ♀