# F1115-704 Safety Boot, electrical protection

SB - BOA® Fit System

MASCOT® FOOTWEAR ELECTROSAFE

09

| | | | | | | |
|---|---|---|---|---|---|---|
| 0836 | 0837 | 0838 | 0839 | 1040 | 1041 | 1042 |
| 1043 | 1044 | 1045 | 1046 | 1047 | 1048 | 1049 |
| 1050 | | | | | | |



E Shock-absorbing
PS Textile nail protection (Ø=3mm)
SR Slip resistant
FO Oil and fuel resistant sole
HRO Heat-resistant outsole compound
WPA Water repellent and breathable
EH Electrical hazard protection

- BOA® Fit System on the side of the boot for quick and easy adjustments.
- Electrically insulating soles protect you from electrical hazards.
- Shock-absorbing, light and flexible EVA midsoles provide extra comfort all through the working day.
- Rubber outer sole that’s heat-resistant up to 300°C contact heat.
- Water-repellent and durable upper in a tightly woven microfibre.
- Composite toe cap and TPU-reinforced scuff cap ensure the necessary protection and make the shoes extra durable.

## Technical info

Developed with the electric vehicle and energy industry in mind with special electrically insulated soles. Dissipative of electrical hazards. Lightweight. Breathable. Water-repellent. Opens and fastens with BOA® Fit System, which consists of a rotational dial, lace and guides. Composite toe cap. TPU toe reinforcement. MASCOLAYER® textile nail protection. Shock-absorbing, light and flexible insole. Insoles are removable. Shock-absorbing EVA midsole. Slip resistant rubber outsole. The sole is oil and petrol resistant. Heat resistant sole up to 300°C contact heat.

## User

## Main material/upper material

Polyamide

Size 42: 620 g

BOA MASCOLAYER®

## Certifications

SB PS SR FO HRO WPA EH

EN ISO20345

- Safety Class SB
- Textile nail protection (Ø=3mm) (PS)
- Slip resistant (SR)
- Oil and fuel resistant sole (FO)
- Heat-resistant outsole compound (HRO)
- Water repellent and breathable (WPA)
- Electrical insulation, ASTM F2413-24 (EH)
- EN ISO 20345: 2022