F1122-901 Safety Shoe

S3S - touch fastening

MASCOT® FOOTWEAR INDUSTRY



09

1140	1141	1142	1143	1144	1145	1146
1147	1148	1149	1150			

Main material/upper material

Nubuck

Size 42: 649 g

HRO Heat-resistant outsole compound
HI Heat insulation
SR Slip resistant
SC Scuff cap abrasion
LG Ladder grip
FO Oil and fuel resistant sole
A Antistatic
E Shock-absorbing
PS Textile nail protection (Ø=3mm)
WPA Water repellent and breathable

MASCOLAYER®

- Extremely durable safety shoe suitable for wearing while welding.
- Long life, with flame retardant thread used in seams.
- Rubber outer sole that’s heat-resistant up to 300°C contact heat.
- Reflective features increase your safety during your working day.

Technical info

Fastening with hook and loop band. Extra protective flap. Composite toe cap. MASCOLAYER® textile nail protection. Midsole made with PU. Sole made of rubber with extreme slip resistance. Heat resistant sole up to 300°C contact heat. Insoles are removable. Shock absorbing insole. Heel cap.

User

♂

Certifications

S3S HRO SR SC LG FO HI

ESD

EN ISO20345

- Safety Class S3S
- Heat-resistant outsole compound (HRO)
- Slip resistant (SR)
- Scuff cap abrasion (SC)
- Ladder grip (LG)
- Oil and fuel resistant sole (FO)
- Heat insulation (HI)
- Electrostatic discharge (ESD)
- EN ISO 20345: 2022